NSN 5935-00-705-2986

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-705-2986 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.034 inches **Overall Height:** 1.125 inches **Overall Width:** 2.312 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.744 inches and 0.756 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.056 inches and 2.068 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 25c3 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 1st contact grouping Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic melamine single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:**

Aluminum alloy

NSN 5935-00-705-2986

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Cadmium and chromium |
| Included Contact Quantity: |
| 3 single mating end 1st contact grouping |
| Included Contact Type: |
| Round socket single mating end 1st contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.025 gold grains, troy and 0.025 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A039b0