NSN 5935-00-706-6269

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-706-6269 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external/internal coupling **Overall Length:** 1.768 inches **Overall Diameter:** 0.809 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Tnc 2nd mating end **Contact Removability:** Nonremovable all mating ends single contact grouping **Shell Type:** Solid **Connector Locking Method:** Friction and externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response all mating ends single contact grouping **Contact Material Specification:** Qq-c-530, comp a federal specification single material response all mating ends single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver

NSN 5935-00-706-6269

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold and body surface silver

Precious Material And Weight:

0.010 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.