NSN 5935-00-706-9494

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-706-9494

view Offilite at https://aerobasegroup.com/hist//3333-00-7-00-3434
Body Style:
Straight shape
Overall Length:
2.635 inches
Overall Height:
0.884 inches
Overall Width:
0.605 inches
Environmental Protection:
Heat resistant and cold resistant
Unthreaded Mounting Hole Diameter:
0.086 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and copper alloy single mating end all contact groupings
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2, cl 2 military specification 1st treatment response single mating end all contact groupings and mil-c-14550 cl 2 military
specification 2nd treatment response single mating end all contact groupings
Torminal Types

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626 composition 22 federal specification single material response single mating end all contact groupings

NSN 5935-00-706-9494

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shell Material Specification:
Qq-s-636 federal specification single material response
Insert Material Specification:
Mil-p-17091 military specification single material response single mating end
Included Contact Quantity:
36 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.