Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-706-9494

Bashy Styles	
Body Style:	
Straight shape	
Overall Length:	
2.635 inches	
Overall Height:	
0.884 inches	
Overall Width:	
0.605 inches	
Environmental Protection:	
Heat resistant and cold resistant	
Unthreaded Mounting Hole Diameter:	
0.086 inches	
Distance Between Mounting Facility Centers:	
2.406 inches	
Mating End Quantity:	
1	
Contact Removability:	
Removable single mating end 1st contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end all contact groupings	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end all contact groupings	
Contact Surface Treatment:	
Gold single mating end all contact groupings and copper alloy single mating end all contact groupings	
Insert Material:	
Plastic polyamide single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204 type 2, cl 2 military specification 1st treatment response single mating end all contact groupings an	d mil-c-14550 cl 2 military
specification 2nd treatment response single mating end all contact groupings	
Terminal Type:	

## **Terminal Type:**

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-626 composition 22 federal specification single material response single mating end all contact groupings

## NSN 5935-00-706-9494

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shell Material Specification:
Qq-s-636 federal specification single material response
Insert Material Specification:
Mil-p-17091 military specification single material response single mating end
Included Contact Quantity:
36 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.