# NSN 5935-00-708-7573

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-708-7573 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, side opening w/clamp **Overall Length:** 3.095 inches **Overall Height:** 1.546 inches **Overall Width:** 0.500 inches **Cable Entrance Diameter:** 0.375 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 41 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 750.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, side opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-00-708-7573

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-14548, type 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365, type 1, grade b federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

## **Insert Material Specification:**

Mil-m-19833, type gdi-30 military specification single material response single mating end

## **Included Contact Quantity:**

41 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

0.041 gold grains, troy and 0.041 silver grains, troy

# **Precious Material:**

Gold and silver

### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

#### **Unit Of Measure:**

### **Demilitarization:**

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-14548 spec.