

View Online at <https://aerobasegroup.com/nsn/5935-00-711-3079>

**Body Style:**

Straight edge type

**Overall Length:**

Between 3.125 inches and 3.132 inches

**Overall Height:**

0.658 inches

**Overall Width:**

Between 0.370 inches and 0.380 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.193 inches and 0.196 inches

**Distance Between Mounting Facility Centers:**

Between 2.803 inches and 2.810 inches

**Board Accommodated Length:**

2.454 inches single board and 2.470 inches single board

**Board Accommodated Width:**

Between 0.198 inches and 0.202 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty mdg military specification single material response single mating end

**Included Contact Quantity:**

74 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.074 gold grains, troy and 0.074 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.