

View Online at <https://aerobasegroup.com/nsn/5935-00-711-3869>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

4.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.875 inches

**Overall Height:**

Between 1.151 inches and 1.161 inches

**Overall Width:**

0.984 inches

**Environmental Protection:**

Corrosion resistant

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.562 inches

**Distance From Mounting Shoulder To Front Face:**

0.625 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

59c10 single mating end

**Contact Removability:**

Removable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 2nd contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end 2nd contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

49 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.059 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.