NSN 5935-00-713-0005

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-713-0005

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.719 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.594 inches
Overall Height:
0.797 inches
Overall Width:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.469 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 40
Thread Size:
0.138 inches and 0.138 inches and 0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-713-0005 Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-male and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0