NSN 5935-00-713-3947

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-713-3947

Body Style:

Straight edge type w/card guide

Overall Length:

3.675 inches

Overall Height:

1.000 inches

Overall Width:

0.453 inches

Distance Between Mounting Facility Centers:

3.300 inches

Board Accommodated Length:

2.200 inches single board

Board Accommodated Width:

0.103 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

2500.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tapered pin single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14f, type mfe military specification single material response single mating end

Included Contact Quantity:

12 single mating end single contact grouping

NSN 5935-00-713-3947

Electrical Receptacle Connector - Page 2 of 2



inciuaea	Contact	туре
Hermanh	radita sina	nla m

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.