

NSN 5935-00-715-1147 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-715-1147 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 3.090 inches **Overall Height:** 1.030 inches **Overall Width:** 0.625 inches **Distance Between Mounting Facility Centers: 2.718 inches Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Turret single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

NSN 5935-00-715-1147

Electrical Receptacle Connector - Page 2 of 2



| Unable To Decode: |
|--|
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Jackscrew type-male and location-left handandjackscrew type-female and location-right hand |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-14 spec. |