Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-716-6728

| | Overall Length: |
|----|--|
| 0 | .825 inches |
| 0 | Overall Height: |
| | .125 inches |
| 0 | Overall Width: |
| 1 | .125 inches |
| Ε | invironmental Protection: |
| N | loisture resistant |
| U | Inthreaded Mounting Hole Diameter: |
| 0 | .120 inches |
| С | Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0 | .906 inches |
| D | istance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0 | .906 inches |
| N | lating End Quantity: |
| 1 | |
| С | Contact Maximum Current Rating In Amps: |
| 7 | .5 single mating end 2nd contact grouping |
| С | Contact Maximum Ac Voltage Rating In Volts: |
| 5 | 00.0 single mating end 2nd contact grouping |
| С | Contact Maximum Dc Voltage Rating In Volts: |
| 7 | 00.0 single mating end 1st contact grouping |
| С | connector Locking Method: |
| В | ayonet latch |
| Ir | nsert Material: |
| R | tubber synthetic single mating end |
| S | hell Material: |
| A | luminum alloy |
| Ir | ncluded Contact Quantity: |
| 1 | 4 single mating end 2nd contact grouping |
| Ir | ncluded Contact Type: |
| R | cound pin single mating end all contact groupings |
| S | helf Life: |
| Ν | l/a |
| U | Init Of Measure: |
| | |
| D | emilitarization: |
| Ν | lo |
| F | iig: |
| A | 039b0 |
| | |