## NSN 5935-00-717-4483

Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-717-4483

| view Offiline at https://defobasegroup.com/nish/0000-00-717-4400                                |
|---|
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Nonremovable single mating end all contact groupings  |
| Contact Maximum Current Rating In Amps:   |
| 7.5 single mating end all contact groupings   |
| Contact Maximum Ac Voltage Rating In Volts:   |
| 650.0 single mating end all contact groupings   |
| Polarization Method:  |
| Mating end  |
| Terminal Location:  |
| Back single mating end all contact groupings  |
| Contact Material:   |
| Copper alloy single mating end all contact groupings  |
| Contact Surface Treatment:  |
| Gold single mating end all contact groupings and silver single mating end all contact groupings |
| Insert Material:  |
| Plastic melamine mineral filled single mating end   |
| Terminal Type:  |
| Solder well single mating end all contact groupings   |
| Shell Material:   |
| Aluminum alloy  |
| Included Contact Quantity:  |
| 3 single mating end 2nd contact grouping  |
| Included Contact Type:  |
| Round socket single mating end 1st contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold and contact surfaces silver   |
| Precious Material And Weight:   |
| 0.020 gold grains, troy and 0.020 silver grains, troy   |
| Precious Material:  |
| Gold and silver   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |
| No  |
| Fiig:   |
|   |

A039b0