

View Online at <https://aerobasegroup.com/nsn/5935-00-720-9922>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

Between 2.110 inches and 2.140 inches

Overall Height:

Between 1.355 inches and 1.395 inches

Overall Width:

Between 1.355 inches and 1.395 inches

Unthreaded Mounting Hole Diameter:

Between 0.118 inches and 0.124 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.057 inches and 1.067 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.057 inches and 1.067 inches

Distance From Mounting Shoulder To Front Face:

Between 0.975 inches and 0.985 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

18-4 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

13.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

900.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

5

Thread Size:

1.125 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

4 1st mating end all contact groupings

Included Contact Type:

Round socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0