NSN 5935-00-721-0607

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-721-0607 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 0.844 inches and 0.906 inches **Overall Height:** Between 1.469 inches and 1.531 inches **Overall Width:** Between 1.469 inches and 1.531 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.151 inches and 1.161 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.151 inches and 1.161 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.765 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-7 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches **Shell Material:**

Aluminum alloy

NSN 5935-00-721-0607

Receptacle Dummy Connector - Page 2 of 2



Snell	Surrace	reatment

Cadmium and chromate

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0