## NSN 5935-00-721-3229

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-721-3229 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** Between 2.469 inches and 2.531 inches **Overall Width:** Between 2.469 inches and 2.531 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.168 inches and 0.183 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.933 inches and 1.943 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.933 inches and 1.943 inches **Distance From Mounting Shoulder To Front Face:** Between 0.875 inches and 0.906 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-1 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-00-721-3229

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.312 inches
Thready Qty Per Inch (tpi):
16
Thread Size:
2.250 inches
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Included Contact Quantity:
4 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.038 gold grains, troy and 0.038 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0