NSN 5935-00-722-4290

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-722-4290

Body Style:
Straight shape, external coupling
Overall Length:
1.125 inches
Overall Height:
1.281 inches
Overall Width:
1.281 inches
Environmental Protection:
Corrosion resistant and pressure proof and vibration resistant and humidity resistant and shock resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.968 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.968 inches
Distance From Mounting Shoulder To Front Face:
0.532 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
27 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment:

NSN 5935-00-722-4290

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromium

Included Contact Quantity:

27 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.027 gold grains, troy and 0.027 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.