NSN 5935-00-723-4486

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-723-4486 **Body Style:** Straight shape, external coupling **Overall Length:** 1.266 inches **Overall Height:** 1.141 inches **Overall Width:** 1.141 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Distance From Mounting Shoulder To Front Face:** Between 0.462 inches and 0.493 inches **Mating End Quantity: Contact Position Arrangement Style:** 10-6 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

Cadmium

Aluminum alloy

Shell Surface Treatment:

NSN 5935-00-723-4486

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Four 0.150 in. Diameter intersected mtg holes spaced 0.812 in. By 0.812 in.

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms3127 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.