NSN 5935-00-723-6859

Contact Surface Treatment:

Gold single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-723-6859

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 0.703 inches |
| Overall Diameter: |
| 0.025 inches |
| Environmental Protection: |
| Moisture resistant and vibration resistant |
| Distance From Mounting Shoulder To Front Face: |
| 0.304 inches |
| Mounting Facility Thickness: |
| 0.097 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| C single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 1.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 400.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| End Application: |
| Communications, Iha; engine, aircraft, f-100-pw-200 (f-16a/b/c/d); spruance class dd (963); milstarsystem; aircraft, b-2 bomber (atb); |
| forrestal class cv virginia class cgn (41) helicopter, carrier based asw, sh-60f; ticonderoga class cg (47) hayes class t-ag 195 |
| Thread Size: |
| 0.190 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |

NSN 5935-00-723-6859

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|---|
| Plastic tetrafluoroethylene single mating end |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Gold |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Coaxial pin single mating end single contact grouping |
| Special Features: |
| Weapon system essential |
| Precious Material And Location: |
| Contact and shell surfaces gold |
| Precious Material And Weight: |
| 0.105 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |