Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-724-4421

Body Style:
Multiple card type
Overall Length:
5.950 inches
Overall Height:
0.810 inches
Overall Width:
0.440 inches
Unthreaded Mounting Hole Diameter:
0.178 inches
Distance Between Mounting Facility Centers:
5.629 inches
Board Accommodated Length:
2.492 inches second board
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Included Contact Quantity:
60 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contract ourfaces gold

Contact surfaces gold



**Precious Material And Weight:** 

0.060 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.