Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-724-7961

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.060 inches

Overall Height:

0.530 inches

Overall Width:

0.280 inches

Environmental Protection:

Vibration resistant

Distance Between Mounting Facility Centers:

0.814 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

20 20-20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end



Contact Surface Treatment Specification:	
Mil-g-45204, type 2, cl 1 military specification 1st treatment response	single mating end single contact grouping
Terminal Type:	
Solder well single mating end single contact grouping	
Contact Material Specification:	
Qq-b-613, comp 24 federal specification single material response sing	le mating end single contact grouping
Insert Material Specification:	
Mil-m-19833, ty gdi-30 military specification single material response s	single mating end
Unable To Decode:	
Unable to decode and unable to decode	
Included Contact Quantity:	
20 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Special Features:	
Jackscrew type-female and location-left handandjackscrew type-male	and location-right hand
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.020 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unc and unc	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	