## NSN 5935-00-724-9862

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-724-9862

View Online at https://aerobasegroup.com/nsn/5935-00-724-9862
Body Style:
Angle, shape, internal coupling
Overall Length:
0.750 inches
Overall Height:
0.750 inches
Overall Diameter:
0.375 inches
Environmental Protection:
Weatherproof
Cable Entrance Diameter:
0.125 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bsm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:

Copper alloy

## NSN 5935-00-724-9862

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365, type 2, gr a federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Reference Number Differentiating Characteristics:
As differentiated by quality controlled per gilfillan dwg g350111
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.