NSN 5935-00-724-9863

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-724-9863

| View Online at https://aerobasegroup.com/nsn/5935-00-724-9863 |
|--|
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Angle, shape, internal coupling |
| Overall Length: |
| Between 1.547 inches and 1.578 inches |
| Overall Height: |
| Between 1.344 inches and 1.375 inches |
| Cable Entrance Diameter: |
| Between 0.435 inches and 0.445 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| N single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling nut |
| Connector Cable Strain Relief Method: |
| Compression nut |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.625 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| |

Plastic tetrafluoroethylene single mating end

NSN 5935-00-724-9863

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver **Shell Surface Treatment Specification:** Qq-s-365, type 2, gr a federal specification single treatment response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.