

View Online at <https://aerobasegroup.com/nsn/5935-00-724-9864>

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45024, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365, type 2 federal specification single treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Special Features:**

Has t shape to accommodate 2 coaxial cables

**Precious Material And Location:**

Contact surfaces gold and body surface silver

**Precious Material And Weight:**

0.105 gold grains, troy and 0.105 silver grains, troy

**Precious Material:**

Gold and silver

**Reference Number Differentiating Characteristics:**

As differentiated by quality controlled per gilfillan dwg g39066351

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45024 spec.