

View Online at <https://aerobasegroup.com/nsn/5935-00-725-1169>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.073 inches and 2.103 inches

**Overall Height:**

0.660 inches

**Overall Width:**

Between 0.479 inches and 0.509 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.847 inches and 1.857 inches

**Distance Between Mounting Facility Centers:**

1.852 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

9w4 single mating end

**Contact Removability:**

Nonremovable single mating end 2nd contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

425.0 single mating end 2nd contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end 2nd contact grouping

**Contact Material:**

Copper alloy single mating end 2nd contact grouping

**Contact Surface Treatment:**

Gold single mating end 2nd contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end 2nd contact grouping

**Terminal Type:**

Solder well single mating end 2nd contact grouping

**Contact Material Specification:**

Qq-b-626a, comp 22 federal specification single material response single mating end 2nd contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416a, type 2, cl2 federal specification all treatment responses

**Shell Material Specification:**

Qq-s-636 federal specification single material response

**Insert Material Specification:**

Mil-m-14, ty sdg military specification single material response single mating end

**Included Contact Quantity:**

5 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.