## NSN 5935-00-727-2223

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-727-2223

**Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 2.375 inches **Overall Diameter:** 1.828 inches **Environmental Protection:** Humidity resistant and corrosion resistant and vibration resistant **Cable Entrance Diameter:** 0.938 inches **Mating End Quantity: Contact Position Arrangement Style:** 61 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 285.0 Shell Type: Solid **Connector Locking Method:** Spring friction **Connector Cable Strain Relief Method:** Cable clamp **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Cadmium

## NSN 5935-00-727-2223

Electrical Plug Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Included Contact Quantity:** 

61 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.061 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0