NSN 5935-00-728-0491

Unthreaded Mounting Hole Diameter:

Body Style:
Multiple card
Overall Length:
3.400 inches
Overall Height:
0.720 inches
Overall Width:
0.440 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-728-0491

0.129 inches
Distance Between Mounting Facility Centers:
3.000 inches
Board Accommodated Length:
2.980 inches single board
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Fixed inter-contact
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type mfh military specification single material response single mating end
Included Contact Quantity:
36 single mating end single contact grouping

NSN 5935-00-728-0491

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Leaf spring single mating end single contact grouping Special Features:

Contacts 1, 2, 5, 6, a, b, e and f removed from connector rear

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.