

View Online at <https://aerobasegroup.com/nsn/5935-00-728-0826>

**Body Style:**

Straight edge type

**Overall Length:**

2.406 inches

**Overall Height:**

0.453 inches

**Overall Width:**

0.531 inches

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Mounting Facility Centers:**

2.134 inches

**Board Accommodated Length:**

1.815 inches single board

**Board Accommodated Width:**

0.074 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

2000.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end

**Included Contact Quantity:**

17 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Special Features:**

Polarizing pin located position 13

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.