NSN 5935-00-728-3239

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-728-3239

Body Style: Rectangular shape **Overall Length:** 1.188 inches **Overall Height:** 0.750 inches **Body Width:** 0.313 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.094 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Contact **Connector Locking Method:** Friction **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic melamine mineral filled single mating end **Terminal Type:** Solder well single mating end all contact groupings **Insert Material Specification:** Mil-m-14, type mme military specification single material response single mating end **Included Contact Quantity:**

Included Contact Type:

Round socket single mating end 2nd contact grouping

4 single mating end 2nd contact grouping

NSN 5935-00-728-3239

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.006 gold grains, troy and 0.006 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.