## NSN 5935-00-728-4628

**Thread Class:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-728-4628

2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
Between 1.547 inches and 1.576 inches
Overall Diameter:
Between 1.453 inches and 1.484 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
21-23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
Insert Position In Deg: 0.0
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi):
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi):
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 6 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping

## **NSN 5935-00-728-4628**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-17091 military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.023 gold grains, troy and 0.023 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-17091 spec.