

View Online at <https://aerobasegroup.com/nsn/5935-00-728-5605>

Body Style:

Straight shape, external coupling

Overall Length:

1.094 inches

Overall Diameter:

0.500 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant and thermal shock resistant and moisture resistant

Cable Entrance Diameter:

0.084 inches

Distance From Mounting Shoulder To Front Face:

0.700 inches

Mounting Facility Thickness:

0.188 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping or gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end and plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver and nickel

Shell Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

L-p-403 federal specification all material responses single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces silver or contact surface gold

Precious Material And Weight:

0.105 silver grains, troy or 0.005 gold grains, troy

Precious Material:

Silver or gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.