

View Online at <https://aerobasegroup.com/nsn/5935-00-729-0288>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.937 inches

Overall Height:

1.313 inches

Overall Width:

1.313 inches

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.963 inches and 0.973 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.963 inches and 0.973 inches

Distance From Mounting Shoulder To Front Face:

0.653 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16s-8 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.438 inches

Thread Size:

1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping and cadmium single mating end single contact grouping

Insert Material:

Ceramic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Tin and cadmium

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Hermetically sealed

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0