

View Online at <https://aerobasegroup.com/nsn/5935-00-729-0772>

**Body Style:**

Straight shape, flush mount

**Overall Length:**

Between 0.802 inches and 0.822 inches

**Overall Height:**

Between 0.995 inches and 1.005 inches

**Overall Width:**

Between 1.995 inches and 2.005 inches

**Environmental Protection:**

Moisture proof

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.495 inches and 0.505 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.775 inches and 1.785 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.083 inches and 0.103 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24c2 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

430.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:**

Plastic melamine single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

22 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.024 gold grains, troy and 0.024 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0