

View Online at <https://aerobasegroup.com/nsn/5935-00-729-0773>

Body Style:

Rectangular shape

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.780 inches

Overall Height:

1.204 inches

Overall Width:

1.000 inches

Environmental Protection:

Moisture proof and salt water resistant

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24c2 single mating end

Contact Removability:

Removable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

435.0 single mating end 2nd contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Insert Material Specification:

Mil-m-14, type cmg military specification single material response single mating end

Included Contact Quantity:

22 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end 2nd contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.024 gold grains, troy and 0.024 silver grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.