NSN 5935-00-729-7222

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-729-7222

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.250 inches
Overall Height:
0.812 inches
Overall Width:
0.438 inches
Distance Between Mounting Facility Centers:
Between 0.930 inches and 0.944 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.266 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

NSN 5935-00-729-7222

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.014 gold grains, troy and 0.014 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.