## NSN 5935-00-729-8296

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-729-8296 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Thru-hole mount **Overall Length:** 1.260 inches **Bushing Diameter:** 1.440 inches **Overall Diameter:** 1.440 inches **Distance From Mounting Shoulder To Rear Face:** 1.100 inches **Mounting Facility Thickness:** 0.160 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 3 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 15.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: **Connector Locking Method:** Latch Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

## NSN 5935-00-729-8296

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Zinc alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
3 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.003 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: