

View Online at <https://aerobasegroup.com/nsn/5935-00-729-8618>

**Body Style:**

Straight shape, rectangular

**Overall Length:**

3.218 inches

**Overall Height:**

Between 0.736 inches and 0.756 inches

**Overall Width:**

0.875 inches

**Environmental Protection:**

Salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

2.875 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

800.0 single mating end single contact grouping

**Polarization Method:**

Shell

**Shell Type:**

Solid

**Connector Locking Method:**

Lever-pin

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Insert Material Specification:**

Mil-m-14, ty mdg military specification single material response single mating end

**Shell Guide Type And Location Designator:**

A pin and c pin and 3 pin and 6 pin

**Included Contact Quantity:**

24 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.024 silver grains, troy

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.