## NSN 5935-00-729-8686

Straight shape, internal coupling w/strain relief

**Body Style:** 

Body Length: 1.893 inches

1.281 inches

**Overall Diameter:** 

Corrosion resistant

**Environmental Protection:** 

**Cable Entrance Diameter:** 

Between 0.490 inches and 0.510 inches

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-729-8686

Mating I	End Quantity:
1	
Contact	t Position Arrangement Style:
16-23 si	ngle mating end
Contact	t Removability:
Nonremo	ovable single mating end all contact groupings
Contact	t Maximum Current Rating In Amps:
7.5 singl	le mating end 2nd contact grouping
Contact	t Maximum Ac Voltage Rating In Volts:
500.0 sir	ngle mating end all contact groupings
Contact	t Maximum Dc Voltage Rating In Volts:
700.0 sir	ngle mating end all contact groupings
Polariza	ation Method:
Key, mu	ultiple key groove
Insert P	Position In Deg:
0.0	
Shell Ty	уре:
Solid	
Connec	tor Locking Method:
Bayonet	t slot
Connec	tor Cable Strain Relief Method:
Cable cl	amp
Feature	s Provided:
Closed e	entry contact
Termina	al Location:
Back sin	ngle mating end all contact groupings
Contact	t Material:
Copper	alloy single mating end all contact groupings
Contact	t Surface Treatment:
Gold sin	igle mating end all contact groupings and copper single mating end all contact groupings
Insert M	laterial:
	chloroprene class cr single mating end

## NSN 5935-00-729-8686

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 federal specification 1st treatment response
Included Contact Quantity:
22 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.023 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0