Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-729-8732

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, flange mount, external coupling
Overall Length:
2.375 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.938 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.938 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-403 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Externally threaded shell

16

Unc

N/a

No Fiig:



Electrical Receptacle Connector - Page 2 of 2 **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): **Thread Size:** 2.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Included Contact Quantity:** 52 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.052 gold grains, troy and 0.052 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Shelf Life: Unit Of Measure: **Demilitarization:** A039b0