NSN 5935-00-731-1907

Aluminum

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-731-1907

Body Style:
Straight shape, flush mount
Overall Length:
1.000 inches
Overall Height:
1.125 inches
Overall Width:
2.312 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.062 inches
Distance From Mounting Shoulder To Front Face:
0.125 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

NSN 5935-00-731-1907

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type ii, class 3 federal specification all treatment responses **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.007 gold grains, troy and 0.007 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.