

View Online at <https://aerobasegroup.com/nsn/5935-00-731-5142>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.750 inches

**Overall Diameter:**

1.141 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

10-19 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

130.0 and 170.0

**Shell Type:**

Potting

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Potting type

**Radio Frequency Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

19 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.019 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.