## NSN 5935-00-731-6352

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-731-6352

**Body Style:** 

Straight type

**Overall Length:** 

Between 2.750 inches and 2.760 inches

**Overall Height:** 

Between 0.395 inches and 0.405 inches

**Overall Width:** 

Between 0.243 inches and 0.253 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.093 inches and 0.103 inches

**Distance Between Mounting Facility Centers:** 

Between 2.460 inches and 2.470 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Solder stud single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:** 

48 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Contacts 13 and 19 removed

## NSN 5935-00-731-6352

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.048 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.