NSN 5935-00-731-7665

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-731-7665 **Thread Class:** За **Thread Direction:** Right-hand **Body Style:** Thru-hole mount **Overall Length:** 0.590 inches **Bushing Diameter:** 0.312 inches **Overall Diameter:** 0.406 inches **Distance From Mounting Shoulder To Rear Face:** 0.562 inches **Mounting Facility Thickness:** 0.064 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 8s-1 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid Thread Length: 0.188 inches Thread Size: 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-731-7665

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|--|
| Copper alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |