Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-732-0335

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.688 inches
Overall Height:
0.796 inches
Overall Width:
0.750 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.468 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
2000.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
2800.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.138 inches and 0.138 inches and 0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Conner allow single moting and single contest grouping

Copper alloy single mating end single contact grouping



	t Surface Treatment:
	ngle mating end single contact grouping Material:
	melamine mineral filled single mating end
	t Surface Treatment Specification:
	5204 military specification single treatment response single mating end single contact grouping
	al Type:
	well single mating end single contact grouping
	To Decode:
	to decode and unable to decode
	ed Contact Quantity:
-	le mating end single contact grouping
	ed Contact Type:
	socket single mating end single contact grouping
-	l Features:
	ew type-male and location-left handandjackscrew type-female and location-right hand
Color:	
Brown	
	us Material And Location:
	surfaces gold
	us Material And Weight:
-	old grains, troy
	us Material:
Gold	
	Series Designator:
Unc and	d unc and unc
Shelf Li	ife:
N/a	
Unit Of	Measure:
Demilita	arization:
No	
Fiig:	
A039b0	
Mil-std	(military Standard):
Mil-g-45	5204 spec.