

View Online at <https://aerobasegroup.com/nsn/5935-00-734-4362>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.714 inches and 2.744 inches

**Overall Height:**

Between 0.419 inches and 0.439 inches

**Overall Width:**

Between 0.479 inches and 0.509 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.086 inches and 0.091 inches

**Distance Between Mounting Facility Centers:**

Between 2.495 inches and 2.505 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25w3 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

3800.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium and chromate

**Insert Material Specification:**

Mil-m-14, type sdc-f military specification single material response single mating end

**Included Contact Quantity:**

3 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.037 gold grains, troy and 0.037 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.