NSN 5935-00-738-1993

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-738-1993 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.680 inches **Overall Height:** 3.953 inches **Overall Width:** 3.390 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.870 inches and 2.880 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** G20 2nd mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 80.0 1st mating end 1st contact grouping **Polarization Method:** 2 polarization posts and polarization boss Shell Type: Solid **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.313 inches **Terminal Location:**

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

NSN 5935-00-738-1993

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic melamine all mating ends
Terminal Type:
Solder well all mating ends all contact groupings
Contact Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response all mating ends all contact groupings
Shell Material:
Aluminum alloy a380.0
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 alloy a380 federal specification single material response
Insert Material Specification:
Mil-m-1, type cmg military specification single material response all mating ends
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.046 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-1 spec.