NSN 5935-00-740-7986

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-740-7986 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.160 inches **Overall Diameter:** 0.687 inches **Environmental Protection:** Humidity resistant and watertight **Distance From Mounting Shoulder To Front Face:** 0.813 inches **Mounting Facility Thickness:** 0.241 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 353.5 single mating end single contact grouping **Polarization Method:** Contact Shell Type: **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Conduit nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **End Application:**

Aircraft tomcat f-14

Thready Qty Per Inch (tpi):

28

NSN 5935-00-740-7986

Electrical Receptacle Connector - Page 2 of 2



Inread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic alkyd single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
No
Fiig:
A039b0