NSN 5935-00-751-9624

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-751-9624 **Body Style:** Straight shape threaded **Overall Length:** 0.853 inches **Overall Diameter:** 1.228 inches **Environmental Protection:** Hermetic **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Mounting Facility Thickness:** 0.031 inches **Mating End Quantity: Contact Position Arrangement Style:** 18-30 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1500.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Ceramic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Surface Treatment:**

Cadmium

Included Contact Quantity:

30 single mating end single contact grouping

NSN 5935-00-751-9624

Electrical Receptacle Connector - Page 2 of 2



I	Incl	hul	ed	Co	ntac	:t]	Γνη	۵.
ı		ıuu	cu	-	IILAV	<i>-</i> L	V	₹.

Round pin single mating end single contact grouping

Special Features:

Solder flange mounted

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.030 gold grains, troy and 0.030 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0