

| 8 8 |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-00-752-27 |
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling w/strain relief |
| Body Length: |
| 2.781 inches |
| Overall Diameter: |
| 1.469 inches |
| Cable Entrance Diameter: |
| 0.656 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 20-27 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 22.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 250.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 1.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Crimp and solder single mating end single contact grouping |
| |

NSN 5935-00-752-2728

Electrical Plug Connector - Page 2 of 2



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0