NSN 5935-00-754-5622

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-754-5622 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.250 inches **Overall Height:** 3.000 inches **Overall Width:** 3.000 inches **Unthreaded Mounting Hole Diameter:** Between 0.172 inches and 0.178 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.375 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 40.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 **Thread Size:**

2.750 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-754-5622

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
3 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.023 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0