

View Online at <https://aerobasegroup.com/nsn/5935-00-755-0877>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Fabrication Method:

Molded

Overall Length:

Between 1.234 inches and 1.266 inches

Overall Width:

Between 0.359 inches and 0.391 inches

Mounting Hole Diameter:

Between 0.138 inches and 0.146 inches

Body Mounting Hole Accommodation Length:

Between 0.797 inches and 0.828 inches

Body Mounting Hole Accommodation Width:

Between 0.391 inches and 0.422 inches

Mounting Hole Style:

Rectangular, w/two mounting holes/slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

2.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

8

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.995 inches and 1.005 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.125 inches

Polarization Type:

Off center hole

Projection Length Below Mounting Surface:

Between 0.203 inches and 0.234 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Features Provided:

Component retaining device

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Contact Position Arrangement Style:

Symmetrical

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Furnished Items And Quantity:

4 screw and 2 lock washer

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300